



BUREAU
VERITAS

TYPE APPROVAL CERTIFICATE
N°VPC-ISO10380-TC-TFL-001-JPN Rev.B

Bureau Veritas Japan, acting as third party inspection body, attests that the design type of an item of corrugated metal hose and hose assemblies identified hereunder has been examined against ISO 10380: 2012 and found to satisfy the provisions of the standard which apply to it.

Manufacturer (name): TOFLE CO.,INC.
TOFLE CO.,INC ./ 1-6-16, Honmachi, Chuo-ku, Osaka, Japan
TOFLE OMEGA FLEX CO.,INC. /
886-1, Kawakami Aza Shiragami, Hagi city, Yamaguchi, 758-0141 Japan.

Address: MITSUWA WELDTECH CO.,INC ./
179-1, Chishirocho, Moriyama, Shiga 524-0034 JAPAN,

Trading Name - Mark TOFLE CO.,INC.

Equipment description: Corrugated metal hoses and hose assemblies (see Annex)

Identification of the approved design type(s) See annex

Versions covered by the approved design type(s) (where applicable) SA-SD (1-10) 8A-50A (see detail Page 2/3)

Conditions for validity Renewal
(Initial : 06-09&22/08/2019)

This certificate, which is valid for 5 years and renewable upon request, is valid, unless changes in the state of the art can challenge the approved design type, until (dd/mm/yyyy): 21/08/2029

This certificate shall be deemed to be void and the manufacturer shall alone bear any consequences pursuant to its use, in case of modification on design type of the equipment or changes in the state of the art, where this may affect conformity with the requirements of the standard or the prescribed conditions for use of the equipment, and generally where the manufacturer fails in particular to comply with any of his obligations under ISO 10380 and Certification Condition which Manufacturer and Bureau Veritas agreed.

Other information (where applicable) Minimum frequency of test for type testing was conducted at
TOFLE OMEGA FLEX
TCF No.2

For the activity carried out for the issuance of the present certificate,
Bureau Veritas Japan took as reference the following manufacturer's
technical book

Existence of an annex to the Type approval certificate N /A
Free text/ référence du document

Date of examination (dd/mm/yyyy): 30 & 31/07/2024 & 02,06,07,08 & 19/08/2024
Surveyor: Keijiro.Miyazono

Made at	On (dd/mm/yyyy)	Approved and Recorded in	Signed by	Signature
Yokohama	19/08/2024 (Rev.B)	JAPAN	Kiejiro Miyazono	

This certificate is subject to the terms of Bureau Veritas General Conditions of Service attached to the agreement signed by the applicant. The present document shall not be reproduced, except in full, without Bureau Veritas Japan and Client's approval.

This revision supersedes certificate

VPC-ISO10380-TC-TFL-001-JPN Rev.A issued on 7Aug,2023
Reason: Renewal of valid date 21/08/2024 to 21/08/2029



BUREAU
VERITAS

Revision : VPC-ISO10380-TC-TFL-001-JPN Rev.B

N°VPC-ISO10380-TC-TFL-001-JPN Rev.B

List of the relevant parts of the technical documentation

Test Reports :No.D-3916(Initial)

Drawings: MNW802614-A, MNW802615-A, MNW802616-A, MNW802617-A

corrugated metal hose certified to ISO10380

Tube Type



Code address	SA - S D (1-10)	sketch Structure: Annular type
Descriptions	Super Annular (Standard)	
Materials	SUS316L,SUS321	
Size	8 A ~ 50 A	
max/min allowable temperature	0 °C ~ 550 °C	

Applicable product and Fittings Type

Number of form Code address		TF-1100 -Temperature	TF-1500 -Temperature	TF-5000 -Temperature	TF-7000 -Temperature	TF-7100 -Temperature	TFR-2000, 3000 -Temperature	Ferrule -Temperature	Pipe end -Temperature
DN	PN (bar)	SUSE	SUSSF	SUSSM	SUSSNM/ SUSSNF	SUSSNM- Rubber fittings	SUSBFSUS SUSBSUS	Ferrule	Pipe end
8A	66.0	○	○	○	○	○	○	○	○
10A	73.0	○	○	○	○	○	○	○	○
15A	50.0	○	○	○	○	○	○	○	○
20A	43.0	○	○	○	○	○	○	○	○
25A	44.0	○	○	○	○	○	○	○	○
32A	37.0	○	○	○	○	○	○	○	○
40A	34.0	○	○	○	○	○	○	○	○
50A	23.0	○	○	○	○	○	○	○	○
sketch									

※ ○ : corrugated metal hose certified to ISO10380

TS / (20°C)に対する軽減定数)	8A	10A	15A	20A	25A	32A	40A	50A
20°C	1	66.0 bar	73.0 bar	50.0 bar	43.0 bar	44.0 bar	37.0 bar	23.0 bar
50°C	0.88	58.1 bar	64.2 bar	44.0 bar	37.8 bar	38.7 bar	32.6 bar	20.2 bar
100°C	0.73	48.2 bar	53.3 bar	36.5 bar	31.4 bar	32.1 bar	27.0 bar	16.8 bar
150°C	0.66	43.6 bar	48.2 bar	33.0 bar	28.4 bar	29.0 bar	24.4 bar	15.2 bar
200°C	0.60	39.6 bar	43.8 bar	30.0 bar	25.8 bar	26.4 bar	22.2 bar	13.8 bar
250°C	0.56	37.0 bar	40.9 bar	28.0 bar	24.1 bar	24.6 bar	20.4 bar	13.8 bar
300°C	0.52	34.3 bar	38.0 bar	26.0 bar	22.4 bar	22.9 bar	19.0 bar	12.9 bar
350°C	0.50	33.0 bar	36.5 bar	25.0 bar	21.5 bar	22.0 bar	17.7 bar	12.0 bar
400°C	0.48	31.7 bar	35.0 bar	24.0 bar	20.6 bar	21.1 bar	18.5 bar	11.5 bar
450°C	0.47	31.0 bar	34.3 bar	23.5 bar	20.2 bar	20.7 bar	17.8 bar	11.0 bar
500°C	0.46	30.4 bar	33.6 bar	23.0 bar	19.8 bar	20.2 bar	17.4 bar	10.8 bar
550°C	0.42	27.7 bar	30.7 bar	21.0 bar	18.1 bar	18.5 bar	15.6 bar	10.6 bar

口径	最小曲径半径 (mm)		使用圧力 (bar)
	固定	繰返し	
8 A	20 mm	60 mm	66.0 bar
10 A	30 mm	100 mm	73.0 bar
15 A	35 mm	125 mm	50.0 bar
20 A	40 mm	130 mm	43.0 bar
25 A	70 mm	190 mm	44.0 bar
32 A	90 mm	205 mm	37.0 bar
40 A	125 mm	235 mm	34.0 bar
50 A	190 mm	270 mm	23.0 bar



**BUREAU
VERITAS**

List of the versions covered (where applicable)

N/A

Annex to the Certificate

N°VPC-ISO10380-TC-TFL-001-JPN Rev.B

TCF No.2